



## DEGREASER – RUFF-STUFF

### Description

TORQ RUFF-STUFF water-based degreaser is a high quality biodegradable concentrate cleaning agent dilutable with water. TORQ RUFF-STUFF degreaser is extremely versatile and can be used safely for removing heavy soils such as oil, grease and grime stains from all types of equipment including on- and off-road vehicles, offshore oil rigs and railway fleets. TORQ RUFF-STUFF is non-flammable and suitable for commercial, industrial and domestic applications.

### Application

- Can be applied by hand, brush, spray or high-pressure cleaning equipment.
- Simply dilute as recommended and apply to surface that requires degreasing & cleaning.
- Ensure agitation with broom, brush or cloth on affected area. Allow product to activate or rest for 1 minute before rinsing with water.
- Can be applied to a wide range of applications including steel cables, wire ropes, engines, gearboxes, pumps, tools and machinery.
- Effective in both soft and hard water applications.

### Benefits

- Cleans without hard scrubbing.
- Effective penetration that rapidly removes heavy soils.
- Biodegradable (Eco-responsible).
- Economical.
- Free rinsing and high foaming.
- All around household & industrial cleaning.

### Green Seal Certification (PENDING)

This product meets Green Seal™ Standard GS-34 based on effective performance and protective limits on: VOCs, ozone depleting chemicals, and human & environmental toxicity. GreenSeal.org



Green Seal® is a global nonprofit organization that pioneered the ecolabeling movement with a mission to transform the economy for a healthier, greener world. For 30 years, Green Seal's rigorous standards for health, sustainability and product performance have driven permanent shifts in the marketplace, empowering better purchasing decisions and rewarding industry innovators.

### Dilution Guide

Dilution guide 1 part of degreaser 1 part of water

Heavy Duty	1:5
Parts Washer	1:10
Workshop Floors	1:20
Domestic Use	1:50



### PRODUCT CHARECTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
FLASH POINT	°C	None	n/a
BOILING POINT	°C	100	ASTM D1120
PH		11-12	ELECTRODES
SPECIFIC GRAVITY		1.090	ASTM D4052
APPEARANCE		transparent	VISIBILITY

The information and figures given here are typical of current production and conform to specification, minor variations may occur.